



Product Features

- 12V Constant Voltage IC LED strip
- High color rendering index CRI>80
- Color range White(2700...6500K)
- Beam Angle :120°
- Adjust the length cuttable after every 82,5mm
- All combinations with constant voltage LED Driver
- Self-cooling (no additional heat sink required)
- Type of protection :IP00
- Life time(L70B50) >50.000 h, at Tc=55°C
- MOQ:20/pcs

Application Areas

- Cove Lighting
- indoor lighting
- Decorative lighting
- Linear Lighting
- Tube Lighting



RESİM HAZIRLANIYOR

General Specifications

Operation Voltage	~12V
Module Driver Type	Constant Voltage
LED Package	3014

Technical Specifications

Length(mm)	498
Width(mm)	12
PCB Thicknes(mm)	1,6
PCB Material	CEM1

Electrical Specifications

Series	3
Parallel	4
Total LED Quantity	12

Connections Data

Wire size	0,35-0,75mm2
Terminal Strip Length	3-4mm
Connection type	Cable soldering

Operating conditions and characteristics

Operating Temperature range	-20 ~ 50°C
Storage Temperature	-20 ~ 80°C

Driving Current & Luminous Flux @(Tj=25°C)

Operating Module Current	Operating Current per LED	Operating Voltage (Typ)	Module Power	2700K			3000K			4000K			5000K			6500K		
				min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.
240mA	40mA	12V	2,9W	307	341	375	322	358	393	337	374	412	348	386	425	348	386	425
360mA	60mA	12V	4,3W	405	450	495	426	473	520	445	494	544	460	511	562	460	511	562
480mA	80mA	12V	5,8W	502	558	614	526	584	643	551	612	673	569	632	696	569	632	696

- Tolerance range for optical and electrical data: $\pm 10\%$.
- Performe can be chone by used heatsink or fixture
- The situation that exceed the specified values, it may
- Due to the special conditions of manufacturing processes of LED, the typical data of technical parameters can only reflect statistical figures and could differ from

The situation that exceed the specified values, it may cause overload and decrease the lifetime of product. Even, it may render unoperational the LED module.

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.