

## Product Features

- 12V Constant Voltage IC LED strip
- High color rendering index CRI>80
- Color range White(2700...6500K)
- Beam Angle :120°
- Adjust the length cuttable after every 31mm
- All combinations with constant voltage LED Driver
- Self-cooling (no additional heat sink required)
- Type of protection :IP00
- Life time(L70B50) >50.000 h, at Tc=55°C
- MOQ:10/pcs

## Application Areas

- Cove Lighting
- indoor lighting
- Decorative lighting
- Linear Lighting
- Tube Lighting

**General Specifications**

Operation Voltage	~12V
Module Driver Type	Constant Voltage
LED Package	3014

**Technical Specifications**

Length(mm)	495
Width(mm)	5
PCB Thicknes(mm)	1,6
PCB Material	FR4 2L

**Electrical Specifications**

Series	3
Parallel	16
Total LED Quantity	48

**Connections Data**

Wire size	0,35-0,75mm2
Terminal Strip Length	3-4mm
Connection type	Cable soldering

**Operating conditions and characteristics**

Operating Temperature range	-20 ~ 50°C
Storage Temperature	-20 ~ 80°C

**Driving Current & Luminous Flux @(Tj=25°C)**

Operating Module Current	Operating Current per LED	Operating Voltage (Typ)	Module Power	2700K			3000K			4000K			5000K			6500K		
				min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.
320mA	20mA	12V	3,84W	389	432	475	389	432	475	423	470	517	458	509	560	458	509	560
400mA	25mA	12V	4,8W	480	533	586	480	533	586	518	576	634	562	624	686	562	624	686
480mA	30mA	12V	5,76W	566	629	692	566	629	692	609	677	744	665	739	813	665	739	813

- Tolerance range for optical and electrical data:  $\pm 10\%$ .
- Performe can be chone by used heatsink or fixture
- The situation that exceed the specified values, it may
- Due to the special conditions of manufacturing processes of LED, the typical data of technical parameters can only reflect statistical figures and could differ from

The situation that exceed the specified values, it may cause overload and decrease the lifetime of product. Even, it may render unoperational the LED module.

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.