



Product Features

- High efficiency 175lm/W
- High color rendering index CRI>80
- Color range White(2700...6500K)
- Beam Angle :120°
- Self-cooling (no additional heat sink required)
- Type of protection :IP00
- Life time(L70B50) >50.000 h, at Tc=55°C
- MOQ:10/pcs

Application Areas

- Decorative Lighting
- Industrial Lighting
- Office lighting



RESİM HAZIRLANIYOR

General Specifications

Operation Voltage	~24V
Module Driver Type	Constant Current
LED Package	5630

Technical Specifications

Length(mm)	280
Width(mm)	24
PCB Thicknes(mm)	1,6
PCB Material	FR4

Electrical Specifications

Series	8
Parallel	3
Total LED Quantity	24

Connections Data

Wire size	0,2-0,75mm2(24-18 AWG)
Terminal Strip Length	7,5-8,5mm
Connection type	Poke-in connector

Operating conditions and characteristics

Operating Temperature range	-20 ~ 50°C
Storage Temperature	-20 ~ 80°C

Driving Current & Luminous Flux @(Tj=25°C)

Operating Module Current	Operating Current per LED	Operating Voltage (Typ)	Module Power	2700K			3000K			4000K			5000K			6500K		
				min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.
250mA	83mA	23,2V	5,8W	855	900	945	897	945	992	938	988	1037	970	1022	1073	970	1022	1073
300mA	100mA	23,8V	7,2W	1054	1110	1165	1111	1170	1228	1162	1224	1285	1206	1270	1333	1206	1270	1333
350mA	116mA	24,2V	8,5W	1239	1305	1370	1301	1370	1438	1358	1430	1501	1401	1475	1548	1401	1475	1548

- Tolerance range for optical and electrical data: $\pm 10\%$.
- Performe can be chone by used heatsink or fixture

- The situation that exceed the specified values, it may

- Due to the special conditions of manufacturing processes of LED, the typical data of technical parameters can only reflect statistical figures and could differ from

The situation that exceed the specified values, it may cause overload and decrease the lifetime of product. Even, it may render unoperational the LED module.

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.