



Product Features

- 24V Constant Voltage IC LED strip
- High color rendering index CRI>80
- Color range White(2700...6500K)
- Beam Angle :120°
- Adjust the length cuttable after every 62mm
- All combinations with constant voltage LED Driver
- Self-cooling (no additional heat sink required)
- Type of protection :IP00
- Life time(L70B50) >50.000 h, at Tc=55°C
- MOQ:10/pcs

Application Areas

- Cove Lighting
- indoor lighting
- Decorative lighting
- Linear Lighting
- Tube Lighting



RESİM HAZIRLANIYOR

General Specifications

Operation Voltage	~24V
Module Driver Type	Constant Voltage
LED Package	3535

Technical Specifications

Length(mm)	310
Width(mm)	10
PCB Thicknes(mm)	1,6
PCB Material	CEM1

Electrical Specifications

Series	6
Parallel	5
Total LED Quantity	30

Connections Data

Wire size	0,35-0,75mm ²
Terminal Strip Length	3-4mm
Connection type	Cable soldering

Operating conditions and characteristics

Operating Temperature range	-20 ~ 50°C
Storage Temperature	-20 ~ 80°C

Driving Current & Luminous Flux @(T_j=25°C)

Operating Module Current	Operating Current per LED	Operating Voltage (Typ)	Module Power	2700K			3000K			4000K			5000K			6500K		
				min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.
300mA	60mA	24V	7,2W	459	510	536	459	510	536	527	586	615	610	678	712	610	678	712
400mA	80mA	24V	9,6W	604	671	705	604	671	705	693	770	809	784	871	915	784	871	915

- Tolerance range for optical and electrical data: $\pm 10\%$.
- Performe can be chone by used heatsink or fixture
- The situation that exceed the specified values, it may
- Due to the special conditions of manufacturing processes of LED, the typical data of technical parameters can only reflect statistical figures and could differ from

The situation that exceed the specified values, it may cause overload and decrease the lifetime of product. Even, it may render unoperational the LED module.

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.