



## Product Features

- 24V Constant Voltage IC LED strip
- High color rendering index CRI>80
- Color range White(2700...6500K)
- Beam Angle :120°
- Adjust the length cuttable after every 100mm
- All combinations with constant voltage LED Driver
- Self-cooling (no additional heat sink required)
- Type of protection :IP00
- Life time(L70B50) >50.000 h, at Tc=55°C
- MOQ:10/pcs

## Application Areas

- Cove Lighting
- indoor lighting
- Decorative lighting
- Linear Lighting
- Tube Lighting



RESİM HAZIRLANIYOR

**General Specifications**

Operation Voltage	~24V
Module Driver Type	Constant Voltage
LED Package	2835

**Technical Specifications**

Length(mm)	500
Width(mm)	16
PCB Thicknes(mm)	1,6
PCB Material	Aluminum

**Electrical Specifications**

Series	6
Parallel	5
Total LED Quantity	30

**Connections Data**

Wire size	0,35-0,75mm2
Terminal Strip Length	3-4mm
Connection type	Cable soldering

**Operating conditions and characteristics**

Operating Temperature range	-20 ~ 50°C
Storage Temperature	-20 ~ 80°C

**Driving Current & Luminous Flux @(Tj=25°C)**

Operating Module Current	Operating Current per LED	Operating Voltage (Typ)	Module Power	2700K			3000K			4000K			5000K			6500K		
				min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.
300mA	60mA	24V	7,2W	653	726	799	653	726	799	694	771	848	734	816	898	734	816	898
400mA	80mA	24V	9,6W	845	939	1033	845	939	1033	896	996	1096	948	1053	1158	948	1053	1158
500mA	100mA	24V	12W	1023	1137	1251	1023	1137	1251	1085	1206	1327	1148	1275	1403	1148	1275	1403

- Tolerance range for optical and electrical data:  $\pm 10\%$ .
- Performe can be chone by used heatsink or fixture
- The situation that exceed the specified values, it may
- Due to the special conditions of manufacturing processes of LED, the typical data of technical parameters can only reflect statistical figures and could differ from

The situation that exceed the specified values, it may cause overload and decrease the lifetime of product. Even, it may render unoperational the LED module.

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.