

Product Features

- High efficiency 160lm/W
- High color rendering index CRI>80
- Color range White(2700...6500K)
- Beam Angle :120°
- Self-cooling (no additional heat sink required)
- Type of protection :IP00
- Life time(L70B50) >50.000 h, at Tc=55°C
- MOQ:10/pcs

Application Areas

- Decorative Lighting
- Industrial Lighting
- Office lighting

General Specifications

Operation Voltage	~12V
Module Driver Type	Constant Current
LED Package	3014

Technical Specifications

Length(mm)	280
Width(mm)	24
PCB Thicknes(mm)	1,6
PCB Material	FR4

Electrical Specifications

Series	4
Parallel	3
Total LED Quantity	12

Connections Data

Wire size	0,2-0,75mm2(24-18 AWG)
Terminal Strip Length	7,5-8,5mm
Connection type	Poke-in connector

Operating conditions and characteristics

Operating Temperature range	-20 ~ 50°C
Storage Temperature	-20 ~ 80°C

Driving Current & Luminous Flux @(Tj=25°C)

Operating Module Current	Operating Current per LED	Operating Voltage (Typ)	Module Power	2700K			3000K			4000K			5000K			6500K		
				min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.
250mA	83mA	11,6V	2,9W	370	390	409	370	390	409	399	420	441	437	460	483	437	460	483
300mA	100mA	12V	3,6W	437	460	483	437	460	483	473	498	522	513	540	567	513	540	567
350mA	116mA	12,2V	4,2W	494	520	546	494	520	546	536	565	593	581	612	642	581	612	642

- Tolerance range for optical and electrical data: $\pm 10\%$.
- Performe can be chone by used heatsink or fixture
- The situation that exceed the specified values, it may
- Due to the special conditions of manufacturing processes of LED, the typical data of technical parameters can only reflect statistical figures and could differ from

The situation that exceed the specified values, it may cause overload and decrease the lifetime of product. Even, it may render unoperational the LED module.

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.