


Product Features

- ♦ 24V Constant Voltage IC LED strip
- ♦ High color rendering index CRI>80
- ♦ Color range White(2700...6500K)
- ♦ Beam Angle :120°
- ♦ Adjust the length cuttable after every 83mm
- ♦ All combinations with constant voltage LED Driver
- ♦ Self-cooling (no additional heat sink required)
- ♦ Type of protection :IP00
- ♦ Life time(L70B50) >50.000 h, at Tc=55° C
- ♦ MOQ:20/pcs

Application Areas

- ♦ Cove Lighting
- ♦ indoor lighting
- ♦ Decorative lighting
- ♦ Linear Lighting
- ♦ Tube Lighting



General Specifications

Operation Voltage	24V
Module Driver Type	Constant Voltage
LED Package	2835

Technical Specifications

Length(mm)	500
Width(mm)	8
PCB Thicknes(mm)	1,6
PCB Material	CEM1

Electrical Specifications

Series	6
Parallel	6
Total LED Quantity	36

Connections Data

Wire size	0,35-0,75mm ²
Terminal Strip Length	3-4mm
Connection type	Cable soldering

Operating conditions and characteristics

Operating Temperature range	-20 - 50 °C
Storage Temperature	-20 - 80 °C

Driving Current & Luminous Flux @(T_j=25 °C)

Operating Module Current	Operating Current per LED	Operating Voltage (Typ)	Module Power	2700K			3000K			4000K			5000K			6500K		
				min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.
200mA	33mA	24V	4,8W	454	504	554	454	504	554	481	534	587	510	567	624	510	567	624
250mA	42mA	24V	6,0W	556	618	680	556	618	680	589	654	719	624	693	762	624	693	762
300mA	50mA	24V	7,2W	653	726	799	653	726	799	694	771	848	734	816	898	734	816	898

- Tolerance range for optical and electrical data: ±10 %.
- Performe can be chone by used heatsink or fixture
- The situation that exceed the specified values, it may
- Due to the special conditions of manufacturing processes of LED, the typical data of technical parameters can only reflect statistical figures and could differ from

The situation that exceed the specified values, it may cause overload and decrease the lifetime of product. Even, it may render unoperational the LED module.

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.