



Product Features

- 12V Constant Voltage IC LED strip
- High color rendering index CRI>80
- Color range White(2700...6500K)
- Beam Angle :120°
- Adjust the length cuttable after every 50mm
- All combinations with constant voltage LED Driver
- Self-cooling (no additional heat sink required)
- Type of protection :IP00
- Life time(L70B50) >50.000 h, at Tc=55°C
- MOQ:10/pcs

Application Areas

- Cove Lighting
- indoor Lighting
- Decorative Lighting
- Linear Lighting
- Tube Lighting



RESİM HAZIRLANIYOR

General Specifications

Operation Voltage	~12V
Module Driver Type	Constant Voltage
LED Package	2835

Technical Specifications

Length(mm)	500
Width(mm)	11
PCB Thicknes(mm)	1,6
PCB Material	Aluminum

Electrical Specifications

Series	3
Parallel	10
Total LED Quantity	30

Connections Data

Wire size	0,35-0,75mm ²
Terminal Strip Length	3-4mm
Connection type	Cable soldering

Operating conditions and characteristics

Operating Temperature range	-20 ~ 50°C
Storage Temperature	-20 ~ 80°C

Driving Current & Luminous Flux @(T_j=25°C)

Operating Module Current	Operating Current per LED	Operating Voltage (Typ)	Module Power	2700K			3000K			4000K			5000K			6500K		
				min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.	min.	Typ.	max.
600mA	60mA	12V	7,2W	653	726	799	653	726	799	694	771	848	734	816	898	734	816	898
800mA	80mA	12V	9,6W	845	939	1033	845	939	1033	896	996	1096	948	1053	1158	948	1053	1158
1000mA	100mA	12V	12W	1023	1137	1251	1023	1137	1251	1085	1206	1327	1148	1275	1403	1148	1275	1403

- Tolerance range for optical and electrical data: $\pm 10\%$.
- Performe can be chone by used heatsink or fixture
- The situation that exceed the specified values, it may
- Due to the special conditions of manufacturing processes of LED, the typical data of technical parameters can only reflect statistical figures and could differ from

The situation that exceed the specified values, it may cause overload and decrease the lifetime of product. Even, it may render unoperational the LED module.

The values contained in this data sheet can change due to technical innovations. Any such changes will be made without separate notification.